

ADIDESCO

RELEASE AGENT FOR ADSORBENT MATERIALS

Description

Release agent formulated based on mineral oils emulsified in water that prevents the adhesion of concrete on formwork of all kinds, but especially on absorbent formwork such as wood, allowing to obtain mortars and concrete with smooth and stain-free surfaces.

Benefits

- Clean removal after concrete setting.
- Saves time and labor when cleaning the formwork.
- Reduces the wear of the wood.
- Economical, high performance and easy handling.
- The life of the formwork is prolonged.

How to use and dosage

- Can be applied several days before forming the formwork or immediately before concreting, since its effectiveness lasts over time.
- There is no waiting period to be respected before pouring the concrete.
- After stripping, it is recommended to clean the treated surface using root brushes and water.
- It is recommended to homogenize the product prior to use.
- Depending on the nature of the support, ADIDESCO has a performance of 10-20m² / L.
- Should be applied on clean and dry formwork using brushes or spray.
- It is supplied ready for use.



Packaging

ADIDESCO can be supplied in 1,000 L containers (IBC), in 25-liter carafes, and in bulk.

Storage conditions

It is recommended to store it in closed containers, protected from environmental contamination and frost, in well-ventilated areas. Do not change the contents of its original container, to prevent possible biological contamination inside.

Maximum period of consumption: 6 months from the date of supply.

The disposal of the product and / or its packaging must be carried out in accordance with current legislation, and is the sole responsibility of the owner and / or end user of the same.

Handling and transportation

Handling this product is not dangerous. The usual preventive measures for handling chemicals must be observed.

Product classified as non-dangerous goods for transport by land, sea or air.

Observations

In order to preserve the quality of the products and ensure their proper performance, it is recommended that customers follow the guidelines that PROQUICESA provides for the application and storage of the products. Notwithstanding the foregoing, PROQUICESA guarantees solely and exclusively that the products comply with the quality established in the technical sheet at the time of delivery, but the customer is and will be responsible for carrying out the proper storage and ensuring the correct application of the same.